

# Diesel Generator Set QSB6.7 Series

160 - 250 kVA, 128 - 200 kW Prime  
CPCB IV+ Emission Compliant



**SHAKTIMAN**



## Latest Technology and Unmatched Performance

- The Cummins® QSB6.7 series rugged engine and world class Stamford alternator powered diesel generator set
- Proven technology with common rail electronic fuel system
- Exhaust after-treatment and in-cylinder solution to meet stringent emission norms
- Superior finish and aesthetics
- Compact in size with optimum power to weight ratio

## Environment Friendly Power

- Class defining and technologically advanced engine to meet stringent exhaust emission norms as per the latest MoEF notification
- The Cummins® diesel generator sets are available with the lowest noise levels in its range

## Lowest Operating Cost and Comprehensive Warranty

- Highly reliable and durable product
- Maximum efficiency even at part loads, offering the advantage of lowest operating costs
- Either 750 or 500 Hours/ 1 year service interval
- Industry acknowledged best-in-class comprehensive warranty on the entire package including rubber components

## Single Source Power Assurance

- All the major components - the engine, alternator, aftertreatment system, control system and canopy are designed, manufactured, and tested by Cummins India
- Best and largest customer support network in India, capable of providing round-the-clock service and spares support

## Engine

- Cummins® QSB6.7 series, 6 cylinder, In-line 4 stroke, radiator cooled engine
- Robust and efficient air handling system with
  - Dry type and replaceable paper element air cleaner with restriction indicator
  - Optimized turbocharger for increased altitude capabilities
- Optimized fuel consumption with common rail electronic injection
- Spin on single fuel filter with water separator
- Cooling system is designed and tested for 50°C ambient conditions
- Full flow spin on lube oil filter
- First fill of lube oil and coolant
- Electrical starter motor with soft start engagement feature
- Battery charging alternator
- 2 x 12 V DC battery



## Alternator

- STAMFORD S3L1D alternator frames from Cummins Generator Technologies
- Brushless type, Screen protected, Revolving field, Self-excited alternator conforming to IS/IEC 60034-1
- Better motor starting capability
- Best in class efficiency
- Compact design with sealed bearings for longer life and lesser maintenance
- Impregnation on all wound components for better mechanical strength

## EATS

- Single module architecture supplied by Cummins Emission Solutions.
- Compact design enabling optimized genset size
- Integrated control module for engine and EATS
- Best in class proven technology for meeting stringent emission norms

## Control Panel

Control panel is powder coated for weather-proof and long-lasting finish. The control panel consists of the following parts:

- PS0602 Controller
- Bus bars with suitable capacity with incoming/outgoing terminals
- Indicating lamps for 'Load ON' and 'Set Running' Instrument fuses duly wired and ferruled.
- MCCB of suitable rating with short circuit protections
- AC/DC separation inside control panel for safety

## PS0602 Features



- Cummins® PowerStart™ PS0602 control is a microprocessor based generator set monitoring, metering and control system with LCD display designed to meet the demands of today's engine driven generator set
- AMF Functionality
- Electronic Governing
- CAN (J1939) Compatible
- Sync Compatible (Capable to accept external speed signal from 3<sup>rd</sup> party sync controller)
- Intuitive operator interface which includes LED backlight 128X64 pixel graphic display with tactile feel soft-switches & generator set status LED lamps
- Remote start-stop
- Audible & Visual warning for Inducement
- Suitable for FAE based engine architecture
- Engine Metering: Oil pressure, Engine temperature, Starting battery voltage, Engine running hours
- AC Alternator Metering: L-L Voltage and L-N Voltage, Current (phase and total), kVA (phase and total) and Frequency. kwh, Total & per phase (kw & kVA), PF, Utility Voltage and Freq
- Engine Protection: Low lube oil pressure, High/Low coolant temperature, Battery High/Low/Weak Volts, Fail to Crank/Start, Sensor failure, Cranking lockout, Low fuel level
- AC Alternator Protection: Over/Under Voltage, Over/Under Frequency, Loss of AC sensing. Overspeed, Over Current, kW Overload
- Data Logging: Engine hours, Control hours and upto 5 recent fault codes
- Configurable glow plug control
- 12/24 Volt DC operation
- Sleep mode
- Modbus interface (RS485 RTU)
- In Power compatible (PC based service tool)
- Certifications - meets the requirement of relevant ISO, EN, Mil Std. and CE standards.
- Maintenance due alarm based on Engine Run Time and due date
- Fuel and DEF level visual display
- Exerciser scheduler

## Silencer

- Hospital Grade Silencer inside canopy with rain cap suitably optimized to meet stringent noise limit
- Silencer specifically tuned to EATS

## Mounting Arrangement

- Engine and alternator are mounted on a common MS fabricated base frame with AVM pads
- Skid mounted radiator
- Base frame with integral fuel tank and DEF tank is provided with drain plug, air vent, inlet and outlet connection and provision for cleaning

## Optional

- Engine: Heated Architecture & HD Air cleaner
- Alternator: PMG and Space Heater
- EATS: Heated Architecture
- Controller: PCC3.3

## Acoustic Enclosure

- Specially designed to meet stringent MoEF/ CPCB norms of 75 dBA@1mtr at 75% load under free field conditions
- The acoustic enclosure is made CRCA sheets in Munsell green shade and a structural/sheet metal base frame painted in black
- 11 tank pretreatment process and UV resistant powder coating of all parts to withstand extreme environment
- High quality noise absorbent and fire-retardant grade acoustic Insulation material (Rockwool) complying to IS 8183
- Top lifting for easy handling at customer site
- External fuel & DEF filling provision

## Remote monitoring system

- Compact & robust device
- Real time DG status & monitoring
- 4G compatible
- Compatible for 12/24 V DC
- Reports & Notification – Alerts & Warning
- Isolated RS 485 interface
- Device location using triangulation

## Technical Data

### Generator Set Specification

Model	CI 160D5P	CI 180D5P	CI 200D5P	CI 225D5P	CI 250D5P
Duty	Prime	Prime	Prime	Prime	Prime
Power Rating kVA / kW	160/128	180/144	200/160	225/180	250/200
No. of Phases	3 Phase				
Output Voltage and Frequency (V and Hz)	415 V, 50 Hz				
Power Factor	0.8 (lagging)				
Current (A)	223	250	278	313	348
RPM	1500	1500	1500	1500	1500

### Engine Specification

Make	Cummins®				
Model	QSB6.7-G21	QSB6.7-G22	QSB6.7-G22	QSB6.7-G23	QSB6.7-G23
Required Power for Rated kVA (hp)	206.8	249.1	249.1	306.9	306.9
Cooling	Liquid Cooled (EG Compleat 50:50)				
DEF	AUS 32 (Premix) as per ISO 22241				
Aspiration	Turbocharged , Intercooled				
No. of cylinders	6, In-line	6, In-line	6, In-line	6, In-line	6, In-line
Bore (mm) x Stroke (mm)	107 X 124	107 X 124	107 X 124	107 X 124	107 X 124
Compression ratio	17.3:1	17.3:1	17.3:1	17.3:1	17.3:1
Displacement (litre)	6.7	6.7	6.7	6.7	6.7
Fuel	High Speed Diesel	High Speed Diesel	High Speed Diesel	High Speed Diesel	High Speed Diesel
Performance class of generator set	ISO 8528-5 G2	ISO 8528-5 G2	ISO 8528-5 G2	ISO 8528-5 G2	ISO 8528-5 G2
Starting system	24 V DC Electrical	24 V DC Electrical	24 V DC Electrical	24 V DC Electrical	24 V DC Electrical
Lube oil specification	CK4	CK4	CK4	CK4	CK4
Lube oil sump capacity, High-Low level (litre)	15-19.5	15-19.5	15-19.5	15-19.5	15-19.5
Total lubrication system capacity (litre)	21.5	21.5	21.5	21.5	21.5
Total coolant capacity(litre)	20.3	20.3	20.3	20.3	21.3
Exhaust pipe size (inch)	5	5	5	5	5
Total wet weight (Engine+Radiator)* (kg)	725	751	751	751	844
Length X Width X Height (Coolpac) (mm)	1534 X 980 X 1219	1466 X 858 X 1132	1466 X 858 X 1132	1466 X 858 X 1132	1517 X 1064 X 1451
Mean Piston speed (m/s)	6.2	6.2	6.2	6.2	6.2
Combustion air intake @100% load (±5%) (cfm)	362	436	436	516	516
Exhaust Temperature (°C)	515	521	521	524	524

Alternator Specification					
Make	STAMFORD (CGT)	STAMFORD (CGT)	STAMFORD (CGT)	STAMFORD (CGT)	STAMFORD (CGT)
Alternator Frame	S3L1D-F41	S3L1D-G41	S3L1D-H41	S3L1D-J41	S3L1D-K41
Enclosure	IP 23	IP 23	IP 23	IP 23	IP 23
Voltage regulation (Max.)	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
Class of Insulation	H Class	H Class	H Class	H Class	H Class
Winding Pitch	2/3	2/3	2/3	2/3	2/3
Stator Winding	Double layer concentric				
Rotor	Dynamically Balanced				
Waveform distortion/ Total Harmonic Distortion	No load < 1.5%, Non distorting balanced linear load < 5 %				
Maximum Unbalanced Load across phases	less than or equal to 25%				
Telephonic Harmonic factor	< 2%				

Rating Definitions	Conformance Standards
<p>Prime Power (PRP): Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528.</p>	<ul style="list-style-type: none"> <li>• IS/IEC 60034-1</li> <li>• ISO 1460</li> <li>• ISO 8528</li> <li>• ISO 3046</li> <li>• ISO 9001</li> <li>• ISO 13018</li> </ul>

Typical Enclosed Genset Dimensions							
Genset Model	Rating (kVA)	Length (mm)	Width (mm)	Height (mm)	Wet Weight" (kg)	DEF Tank Capacity (litre)	Standard Fuel tank Capacity (litre)
CI 160D5P	160	4050	1350	1850	3025	60	385
CI 180D5P	180	4050	1350	1850	3055	60	385
CI 200D5P	200	4050	1350	1850	3120	60	385
CI 225D5P	225	4050	1350	1850	3170	60	385
CI 250D5P	250	4050	1350	2000	3180	60	395

"Approximate Weight

**Powerica Sales Office**

**Toll Free Number: +91 1800 2666036**

Head Office: +91 22 66562525 | +91 22 4315 2525

Ahmedabad: +91 7926468550

Aurangabad: +91 2406601921

Bengaluru: +91 22 22257338

Chennai: +91 44 42422222

Coimbatore: +91 4222205300

Goa: +91 8322438587

Kochi: +91 4842353595

Hyderabad: +91 9849796100

Kolhapur: +91 9011124488

Madurai: +91 4524200081

Nagpur: +91 7126631089

Pune: +91 20 67488299

Mumbai: +91 9821013074

Vijayawada: +91 8790100552

Visakhapatnam: +91 8790100556

Belapur: +91 9833314448

Mysore: +91 9686447100

Rajahmundry: +91 8190100858

Authorised Representative



Visit our Facebook page at :  
Cummins Power Generation India



"Our energy working for you."

Cummins is registered trademarks of Cummins Inc.  
Specifications are subject to change without notice.  
PSBU/CPCB IV+/QSB6.7/Rev-00/07 2023



**Cummins India Limited  
Power Systems Business**

Cummins India Office Campus  
Tower-A, 8<sup>th</sup> Floor, S. No. 21  
Balewadi, Pune - 411 045 (India)

Email : [cpgindia@cummins.com](mailto:cpgindia@cummins.com)  
[www.cummins.com](http://www.cummins.com)



**Powerica Limited**

9th Floor, Bakhtawar, Nariman Point,  
Mumbai – 400 021

Email : [atp@powericaltd.com](mailto:atp@powericaltd.com)  
[www.powericaaltd.com](http://www.powericaaltd.com)